


## BLUESTONE

	<b>Origin</b>	China
	<b>Petrographic classification</b>	Sedimentary rocks - biochemical sedimentary rocks - Fossil limestone (EN 12670)
	<b>Appearance</b>	Blue gray base colour in which round and irregular sedimentary particles are visible. The surface has a speckled structure.
	<b>Alternative names</b>	

### Usage

<b>General</b>	<p>The stone and surface finish should be selected depending on the intended use.</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; background-color: black; color: white; text-align: center; padding: 5px;"><b>Internal Applications</b></td> <td style="width: 50%; background-color: black; color: white; text-align: center; padding: 5px;"><b>Outdoor Applications</b></td> </tr> <tr> <td style="border: 1px solid black; padding: 10px; min-height: 80px;">                     - Wall cladding                 </td> <td style="border: 1px solid black; padding: 10px; min-height: 80px;">                     - Facade cladding                 </td> </tr> </table> <p style="margin-top: 10px;">- This material is only available as brick slips and / or mosaic.</p>			<b>Internal Applications</b>	<b>Outdoor Applications</b>	- Wall cladding	- Facade cladding
<b>Internal Applications</b>				<b>Outdoor Applications</b>			
- Wall cladding				- Facade cladding			
<b>Applications</b>							
<b>Recommendations</b>							

Hardness (Mohs)	Weight	Water absorption	Porosity
			
NPD*	NPD*	NPD*	NPD*
Compressive strength	Flexural strength	Wear resistance	FROSt RESISTANCE
			
NPD*	NPD*	NPD*	NPD*

NPD\*: geen technische gegevens beschikbaar - no technical data available - pas d' informations techniques disponibles

### Observations and recommendations

<ul style="list-style-type: none"> <li>- Shades of color and / or granulometry may be present between the different batches and even within the same batch.</li> <li>- Veins and / or fossils may appear due to geological formation. These are not technical defects and they are part of the material.</li> <li>- The stone also contains stylolitic veins that may emerge after some time. This phenomenon is part of the structure of the material and has no influence on the durability of the stone.</li> <li>- Due to the mineralogical composition, this material is not resistant to acids.</li> </ul>
--

### Installation

# BLUESTONE

<b>General</b>
<b>Installation system</b>
<b>Joint Width</b>
<b>Maintenance</b>

General procedures of good workmanship should be followed when laying the tiles (cfr. BBR: Belgian Building & Research Institute ref. 137 Guide for Installing - Natural Stone and ref. 213). Immediately after delivery, the material will be stored indoors or at least protected from rain, wind and frost. If slabs are damaged or broken, the supplier must be informed before installation. They will then be used, as far as possible, against walls or for certain cuts.

Before installation, the installer will examine the slabs (previously dried) with the client and / or the architect to check for any deviations from the samples. The slabs will be carefully mixed before laying, in order to obtain a harmonious distribution of colors and various shades of the material.

Important: "Installation means acceptance!", It means that AFTER the installation, no more claims will be possible, except for hidden defects.

Flooring Inside

Exterieur Flooring
Not suitable for outdoor paving

## Maintenance

<b>General</b>
<b>First cleaning</b>
<b>Regular maintenance</b>
<b>Protection</b>
<b>Recommendations</b>

For more information on maintenance, see the document entitled "Care instructions" (available from us). We recommend that you follow these instructions so as not to damage the stone. The products used must be suitable for the materials. Follow the manufacturer's advice. In general, it must be stated that no moisture may be exaggerated when maintaining natural stone!

First cleaning with a suitable cleaning agent (eg Lithofin Multi-Cleaner - note: does not contain acid) applicable one week after rejoining the floor. If a cement veil should appear, use the same product combined with a single-disc machine.

Use for regular maintenance a product suitable for natural stone, such as Lithofin Wash & Clean. In order to better protect the surface finish, we advise to treat it periodically (1 to 2 times per month) with a nourishing product for natural stone, such as Lithofin Care-Sheen.

When the floor is completely dry we strongly recommend to protect sensitive areas (kitchen, bathroom, etc.) with a suitable sealer (e.g. Lithofin Stain Stop 'W').

Do not use any acid-based products for the maintenance of this natural stone.